

Pneumatic **MK** Dispenser TS493X

2-K 600 ml 1:1 SBS Cartridge



Suitability <ul style="list-style-type: none"> • Force 4 kN (~400 kg), Air Supply 8 bar (116 PSI), Air Consumption max. 40 litres/min. • 2-Component Cartridge, 600 ml • Material Viscosity High • Professional Use 	[mm]	1:1	
	a	217,0	
	b	51,0	
	c	102,0	

Part Number	Article	Description	Packaging
DP2 600-40-100	151790	Weight 2.58 kg, Length 535 mm Reinforced Nylon Handle, Metal Cartridge Holder, Aluminium Air Cylinder, Quick reloading	1 unit

Product advantages	Customer benefits
Air operated plunger retraction	Quick cartridge exchange
One hand pressure adjustment	Simple dispensing speed adjustment, also during working
Centered handle	Well balanced dispenser for precise working
AntiDrip	Clean application

Headquarters

Sulzer Mixpac Ltd
phone +41 81 772 20 00
fax +41 81 772 20 01
mixpac@sulzer.com
www.sulzer.com

Denmark

Sulzer Mixpac Denmark A/S
phone +45 43 600 111
mail.mk@sulzer.com
www.sulzer.com

USA, South America, Canada and Mexico

Sulzer Mixpac USA Inc.
phone +1 603 893 27 27
fax +1 603 893 37 37
info@SulzerMixpacUSA.com
www.sulzer.com

UK and Ireland

Sulzer Mixpac UK
phone +44 1536 31 29 90
fax +44 1536 31 29 85
mixpac@sulzer.com
www.sulzer.com

Asia Pacific

Sulzer Mixpac China
phone +86 21 6430 68 68
fax +86 21 6430 66 88
mixpac@sulzer.com
www.sulzer.com